ahn ® my Lab

Clinical Centrifuge 4500 RPM **CLC-02**

Usage - the centrifuge is design to separate, sediment, spin down aqueous solutions and solvent suspensions of different sensitivity

High-tech microprocessor - Advanced technology microprocessor dependable accuracy and precision with each spin cycle

Intuitive user controls - User-facing control panel provides quick access to all device features for quick and easy programming of the clinical centrifuge


Maintenance-free DC motor - Brushless DC motor with variable speeds provides reliable performance with minimum maintenance or downtime

Combi rotor - Convenient 8-slot rotor design fits 8 x 15 mL or 4 x 50 mL tubes at maximum capacity

Excellent safety features - Low noise, imbalance detection, and lid-lock safety mechanisms help to maintain an accidentfree laboratory environment

Compact and portable - Space-saving centrifuge design takes up a small amount of the workbench while a lightweight chassis makes it easy to move from one point to another





Ordering information

myLab® CLC-02 Clinical Centrifuge 4500 RPM	7-011-00-0
Portable Cable	7-011-00-0-001

- Grapio Gabio	7 011 00 0 001
Delivery Package	
1 pc. Clinical centrifuge 4500 RPM	
1 pc. 8-slots rotor (pre-installed)	
1 pc. Power supply adaptor	
1 pc. T-Allen Key	
4 pcs. 15 mL Reduction Adaptors	
8 pcs. Reduction adaptors and space	er
1 pc. Instruction manual	
1 pc. Warranty card	

Specifications	
Motor type	Brushless DC motor
Speed	500 to 4500 RPM
Speed accuracy	± 100 RPM
Max. volume	4 x 50 mL tubes
Timer setting	1 – 99 mins and infinity
Noise level	≤ 62 dB (A)
Weight	4 kg (with rotor)
Dimensions (WxDxH)	330x265x161 mm
Lid-lock	Yes
Imbalance detection	Yes







