



CLINICAL CENTRIFUGE



CAPP Rondo Clinical Centrifuge is a compact and reliable low-speed centrifuge, ideal for blood centrifuge applications involving volumes below 15 mL. It stands out in its category for having great features that ensure an easy-to-use, reliable, safe performance.

Features

- Rotor capacity of up to 8 x 15 mL tubes on a fixed-angle rotor
 - Smart airflow design reduces noise
 - Precise RPM setting with increments from 100 RPM and setting from 500-6500 RPM
- Built with a long-life brushless DC motor and a microprocessor
- Can accommodate widely used blood collection tubes due to included adaptors for 5 mL, 7mL, 1.5 mL and 2 mL tubes
 - Digital display with speed and timer indicator
 - Automatic imbalance detection
- Lid lock safety lid opens automatically after the operation is completed
 - Functions countdown timer / RPM/RCF speed setting / error display

With Optional Accessory





Rotor

Specifications

Speed 500 - 6500 RPM / 3873 x g (max. RCF) Speed Accuracy ±100 RPM Motor Type Brushless DC Motor Time Setting 1 to 30 min and infinite mode Imbalance Detection Yes Noise Level < 60 dB Acceleration Time 43 ± 2 sec. Deceleration Time 40 ± 2 sec. Display Yes Dimensions (W x D x H) 260x 244 x 203 mm Weight 4kg (with rotor) Power Consumption 100 W	•	
Motor Type Brushless DC Motor Time Setting 1 to 30 min and infinite mode Imbalance Detection Yes Noise Level < 60 dB Acceleration Time 43 ± 2 sec. Deceleration Time 40 ± 2 sec. Display Yes Dimensions (W x D x H) 260x 244 x 203 mm Weight 4kg (with rotor)	Speed	,
Time Setting 1 to 30 min and infinite mode Imbalance Detection Yes Noise Level 40 ± 2 sec. Deceleration Time 40 ± 2 sec. Display Yes Dimensions (W x D x H) Weight 4kg (with rotor)	Speed Accuracy	±100 RPM
Imbalance Detection Yes Noise Level < 60 dB Acceleration Time 43 ± 2 sec. Deceleration Time 40 ± 2 sec. Display Yes Dimensions (W x D x H) 260x 244 x 203 mm Weight 4kg (with rotor)	Motor Type	Brushless DC Motor
Noise Level < 60 dB Acceleration Time 43 ± 2 sec. Deceleration Time 40 ± 2 sec. Display Yes Dimensions (W x D x H) 260x 244 x 203 mm Weight 4kg (with rotor)	Time Setting	1 to 30 min and infinite mode
Acceleration Time 43 ± 2 sec. Deceleration Time 40 ± 2 sec. Display Yes Dimensions (W x D x H) 260x 244 x 203 mm Weight 4kg (with rotor)	Imbalance Detection	Yes
Deceleration Time 40 ± 2 sec. Display Yes Dimensions (W x D x H) 260x 244 x 203 mm Weight 4kg (with rotor)	Noise Level	< 60 dB
Display Yes Dimensions (W x D x H) 260x 244 x 203 mm Weight 4kg (with rotor)	Acceleration Time	43 ± 2 sec.
Dimensions (W x D x H) 260x 244 x 203 mm Weight 4kg (with rotor)	Deceleration Time	40 ± 2 sec.
Weight 4kg (with rotor)	Display	Yes
	Dimensions (W x D x H)	260x 244 x 203 mm
Power Consumption 100 W	Weight	4kg (with rotor)
	Power Consumption	100 W

Scope of Delivery

1 pc. Clinical Centrifuge	
1 pc. 8-slots Fixed Angle Rotor (Pre-installed)	
1 pc. Power Adapter	
1 pc. T-Allen Key	
8 pc. Reduction Adaptors	
8 pc. Tube Holder and Rubber Cap	
1 pc. User Manual	
1 pc. Warranty Card	

Ordering Information

Cat. No.	Description
CRC-658	CAPP Rondo Clinical Centrifuge 6500 RPM / 3.873 x g for 8 x 15 mL
CRC-658- 0006	Portable Cable