

CAPP Rondo

UNIVERSAL CENTRIFUGE

The CAPP CRC-1544UC is a versatile centrifuge built for universal lab applications requiring high performance & precision. Ideal for research labs and clinical diagnostics, it combines ergonomic design with powerful functionality. With a max speed of 15000 RPM and compatibility with both swing-out and fixed angle rotors

Features

- Brushless, maintenance-free DC motor runs at high speeds of up to 15000 RPM, delivering powerful yet quiet performance
- Flexible operation with adjustable speed from 500–15000 RPM and time setting from 30 seconds to 999 minutes with infinite mode
- Microprocessor controlled for superior accuracy and repeatability
 - Lid-lock safety mechanism opens automatically after every run
- Smart imbalance detection with automatic cut-off ensures safety
- 9 Acceleration & 9 Deceleration modes protect delicate samples
 - One-touch RPM/RCF conversion and short spin feature for ultrafast pelleting
- Intuitive large backlit digital LCD display with last-run memory
- Emergency lid release and low loading height for user convenience
 - Smart airflow design prevents chamber overheating
 - Multiple rotor options (fixed angle & swing-out) for flexible applications
- Stainless steel rotor chamber is corrosion-resistant and easy to clean




Specifications

Speed	500–15000 RPM / RCF varies per rotor (up to 22388 g)	Imbalance Detection	Yes
Motor Type	Brushless DC	Lid Lock Safety	Yes (auto-open after run)
Display	Backlit Digital LCD	Noise Level	<72 dB
Speed Accuracy	±100 RPM	Dimensions (W x D x H)	475 x 585 x 325 mm
Time Setting	30 sec – 999 min. & infinite mode	Weight	24 kg (without rotor)
Speed steps	100 RPM	Acceleration / Deceleration	9 modes each
Ambient Temperature	5 - 40 °C	Rotors	Fixed angle and swing-out options available

Scope of Delivery

1 pc. CRC-1544UC Refrigerated Centrifuge	1 pc. User Manual
1 pc. Power Adapter	1 pc. Warranty Card

CR-15-44UC-UCR Fixed Angle Rotor 44 x 2 mL, RCF up to 22388 x g		CR-15-6UC-UCR Fixed Angle Rotor 6 x 50 mL, RCF up to 2834 x g
CR-15-24UC-UCR Fixed Angle Rotor 24 x 15 mL, RCF up to 2961 x g		CR-15-4UC-UCR Swing Out Rotor 4 x 50 mL, RCF up to 3305 x g
CR-15-32UC-UCR Swing Out Rotor 32 x 6 mL, RCF up to 3164 x g		

Ordering Information

Cat No.	Description
CRC-1544UC	CAPP® Rondo Universal Centrifuge, 15000 RPM
Rotor Options	
CR-15-44UC-UCR	Fixed Angle Rotor 44 x 2 mL, max. RPM 15000 / RCF up to 22388 x g
CR-15-6UC-UCR	Fixed Angle Rotor 6 x 50 mL, max. RPM 4500 / RCF up to 2834 x g
CR-15-24UC-UCR	Fixed Angle Rotor 24 x 15 mL, max. RPM 4500 / RCF up to 2961 x g
CR-15-4UC-UCR	Swing Out Rotor 4 x 50 mL, max. RPM 4500 / RCF up to 3305 x g
CR-15-32UC-UCR	Swing Out Rotor 32 x 6 mL, max. RPM 4500 / RCF up to 3164 x g